



METAL X

PRODUCT SPECIFICATIONS

The Metal X is a revolutionary 3D printer that prints metal powder bound in a plastic matrix to eliminate safety risks associated with traditional metal 3D printing methods while enabling new features like close-cell infill for reduced part weight and cost. It's up to 10x less expensive than alternative metal additive manufacturing technologies — and up to 100x less than traditional fabrication technologies like machining or casting. Affordable, reliable, and easy to use, the Metal X print system gives you everything you need to go from design to fully functional metal parts faster than ever before.

Atomic Diffusion Additive Manufacturing (ADAM) 300 x 220 x 180 mm (11.8 x 8.7 x 7.1 in) 575 x 467 x 1,120 mm (22.7 x 18.4 x 44.1 in), 75 kg (160 lbs) Heated Heated, vacuum-sealed print sheet, auto bed leveling Two nozzles — Metal material and release material 100–240 VAC, 2,400 W (20 A peak), IEC 60320 type C20 Stainless steel (17-4 PH, 316L*), tool steel (H13, A2, D2*), Titanium Ti6Al4V*, Inconel (IN) 625*
575 x 467 x 1,120 mm (22.7 x 18.4 x 44.1 in), 75 kg (160 lbs) Heated Heated, vacuum-sealed print sheet, auto bed leveling Two nozzles — Metal material and release material 100–240 VAC, 2,400 W (20 A peak), IEC 60320 type C20 Stainless steel (17-4 PH, 316L*), tool steel (H13, A2, D2*),
Heated Heated, vacuum-sealed print sheet, auto bed leveling Two nozzles — Metal material and release material ents 100–240 VAC, 2,400 W (20 A peak), IEC 60320 type C20 Stainless steel (17-4 PH, 316L*), tool steel (H13, A2, D2*),
Heated, vacuum-sealed print sheet, auto bed leveling Two nozzles — Metal material and release material ents 100–240 VAC, 2,400 W (20 A peak), IEC 60320 type C20 Stainless steel (17-4 PH, 316L*), tool steel (H13, A2, D2*),
Two nozzles — Metal material and release material 100–240 VAC, 2,400 W (20 A peak), IEC 60320 type C20 Stainless steel (17-4 PH, 316L*), tool steel (H13, A2, D2*),
ents 100–240 VAC, 2,400 W (20 A peak), IEC 60320 type C20 Stainless steel (17-4 PH, 316L*), tool steel (H13, A2, D2*),
Stainless steel (17-4 PH, 316L*), tool steel (H13, A2, D2*),
Ceramic (consumed at 1:10 ratio to metal spools, on average)
Filament fed, bound powder
250 x 183 x 150 mm (9.8 x 7.2 x 5.9 in), 10kg
Metal material with ceramic release layer
50μm and 125μm post-sinter
re Eiger Cloud (Other options available at cost)
Two-factor authentication, org admin access, single sign-on
V SIDE VIEW

All specifications are approximate and subject to change without notice.

22"





^{*} Materials currently under development.